

Passive PDU-40HE (KPMDU-EM-xxxxC13C19-x-32)

PDF-Export



Type	KPMDU-EM-2406C13C19-1-32 (7.3kVA) KPMDU-EM-2406C13C19-3-32 (22kVA) KPMDU-EM-4800C13C19-1-32 (7.3kVA) KPMDU-EM-4800C13C19-3-32 (22kVA)
Nominal power, voltage	max. 22kVA, 230/400V, depending on configuration
Conector plug	IEC60309, CEE-32A, L1/L2/L3/N/PE/6h
Connection cable	Length: 3m, rubber hose H07RN-F-5G6
Sockets C13 (IEC60320)	24 / 48
Sockets C19 (IEC60320)	6 / 0
Locking	IEC-LOCK for C13/C19
Fuse/circuit breaker	3/6 x 10A C-type, interlocked, monitored 3x 16A C-type, interlocked, monitored
Optical signaling	Red/Green for fuse error
Chassis	Sheet metal, powder-coated RAL9005, protection class 1, protection rating IP20
Dimensions	1770 x 78.2 x 62.5mm (HxWxD)
Weight	ca. 9kg
Environmental conditions	-10°C to 55°C, humidity 5-95% Storage temperature: -20°C to 60°C
Approvals	CE (2014/35/EG, 2011/65/EU)
Electrical security	DGUV-V3 test, VDE 0105-100
Marking	Serial number (bar code) additional free marking area front plate (60x20mm)
Content of delivery	<ul style="list-style-type: none"> • PDU with 3m cable and connector • mounting material: 3x angle brackets, 12x countersunk-head screws M3x15 • inspection protocol