

AccessManager (KXP-16)

PDF-Export



Connectivity	Stand-Alone or in combination with AlarmManager
Number of doors	Up to 16 DorrLock devices (radio)
Networking	Up to 999 AccessManagers in Master-Slave mode linkable. Management through master AccessManager.
Internal memory	5.000 persons - access permissions 100 door profiles 100 time profile (daytime, weekday)
SD card	Integrated Micro SD card holder up to 128 GB
Internal buzzer	85dB, 2.3kHz
LED	ALARM (red), RUN (green), LINK/ACT at LAN connector
LAN (PoE)	10/100 Mbit LAN interface with PoE, integrated Web-Server Ports: 443 TCP (HTTPS), 5222 TCP (Kentix360), 161 UDP (SNMP-GET, 162 UDP (SNMP-TRAP)
Power supply (PoE)	PoE class 2, Power consumption approx. 3W
Wireless DoorLock	868MHz, Encryption AES 128 Bit, Distance up to 25m depending on building structure and environment up to 16 DoorLock-devices per AccessManager
KENTIX System port	RJ45, for the connection of external Kentix Plug´n Play modules
Alarm system control	Control with Kentix AlarmManager over Ethernet Control of external intrusion alarm systems only via I/O contacts
Chassis	Material: PS 90 x 90 x 45 mm, weight approx. 100g Color: Carbon black
Environmental conditions	Temperature 0 to 50°C, humidity 5-95%, non-condensing With outdoor chassis up to -20°C possible
Types	KXP-16-B (chassis Black) KXP-16-W (chassis white)
Content of delivery	Mounting bracket, mounting material, antenna, SlimLine cable 3m
Accessories	PoE Injector (KPOE150S) Power Adapter with power supply (KIO1, KIO3)
Approvals	CE