

DoorLock-DC PRO (KXC-KN4)

PDF-Export



DoorLock-DC	Radio door knob according to DIN15684
Connectivity	DoorLock AccessManager KXP-16
RFID Reader	13.56MHz Mifare Classic, DESfire
Internal buzzer	70dB, 2.3kHz
LED	Red, green
Wireless	868MHz, Encryption AES 128 Bit Distance approx. 25m depending on building structure/environment Up to 16 radio door locks per AccessManager
Usage	Inside and outside doors depending on type Suitable for fire and smoke protection doors For > 50 bookings/day
Low-Power-opening	Not required as battery can be accessed through magnetic opening
Assembly / disassembly	Via mechanical inner-knob, battery change through magnetic release
Permanent engagement	Permanent engagement possible without additional power consumption
Power supply	1 x battery CR2 Lithium (3V)
Battery life	up to 45.000 operations or up to 4 years depending on usage
Dimensions knob	Outer knob: length = 44.3mm, diameter = 31.4mm Inner knob: length = 20.0mm, diameter = 29.0mm
Material	nickel-plated brass, antenna: hard plastic
Zylinder lengths	30/30mm to 70/70mm (special lengths up to 200/200mm) For profile cylinders of type DIN 18252
Environmental conditions	Temperature -25°C to 55°C (IP55) Temperature -25°C to 65°C (IP66)
Types	KXC-KN4-INDOOR (IP55) for interior installations without direct weather influence KXC-KN4-OUTDOOR (IP66) for exterior installations
Content of delivery	Radio door knob, Battery (CR2)
Accessories	EURO Profile cylinder, half cylinder, anti-panic cylinder
Approvals	CE
Resistance Class	RC 2