

# Passive PDU-40HE (KPMDU-EM-xxxxC13C19-x-32)

PDF-Export



<b>Type</b>	KPMDU-EM-2406C13C19-1-32 (7.3kVA) KPMDU-EM-2406C13C19-3-32 (22kVA) KPMDU-EM-4800C13C19-1-32 (7.3kVA) KPMDU-EM-4800C13C19-3-32 (22kVA)
<b>Nominal power, voltage</b>	max. 22kVA, 230/400V, depending on configuration
<b>Conector plug</b>	IEC60309, CEE-32A, L1/L2/L3/N/PE/6h
<b>Connection cable</b>	Length: 3m, rubber hose H07RN-F-5G6
<b>Sockets C13 (IEC60320)</b>	24 / 48
<b>Sockets C19 (IEC60320)</b>	6 / 0
<b>Locking</b>	IEC-LOCK for C13/C19
<b>Fuse/circuit breaker</b>	3/6 x 10A C-type, interlocked, monitored 3x 16A C-type, interlocked, monitored
<b>Optical signaling</b>	Red/Green for fuse error
<b>Chassis</b>	Sheet metal, powder-coated RAL9005, protection class 1, protection rating IP20
<b>Dimensions</b>	1770 x 78.2 x 62.5mm (HxWxD)
<b>Weight</b>	ca. 9kg
<b>Environmental conditions</b>	-10°C to 55°C, humidity 5-95% Storage temperature: -20°C to 60°C
<b>Approvals</b>	CE (2014/35/EG, 2011/65/EU)
<b>Electrical security</b>	DGUV-V3 test, VDE 0105-100
<b>Marking</b>	Serial number (bar code) additional free marking area front plate (60x20mm)
<b>Content of delivery</b>	<ul style="list-style-type: none"> <li>• PDU with 3m cable and connector</li> <li>• mounting material: 3x angle brackets, 12x countersunk-head screws M3x15</li> <li>• inspection protocol</li> </ul>