

AccessManager for radio readers - DATASHEET



ORDER-CODES:

KXP-16-B, KXP-16-W, KXP-16-B-BLE, KXP-16-W-BLE

Integrated software	KentixONE via integrated web server (HTTPS)
Number of doors	Up to 16 DoorLock devices (radio)
Networking	Any number of AccessManagers as main satellite
SD card	Integrated Micro SD card holder up to 128 GB
Acoustic signal generator	85dB, 2.3kHz
LED	ALARM (red), RUN (green), LINK/ACT to LAN socket
Network (PoE)	10/100 Mbit Ethernet port with PoE
Power supply (PoE)	PoE class 2, power consumption approx. 3W



Radio 868MHz (depending on version)Radio frequency 868MHz, encryption AES 128 bit, radio range max. 25m depending on building structure/environmentRadio BLE 2.4GHz (depending on version)Radio frequency 2.4GHz, encryption AES 128 bit, radio range max. 20m depending on building structure/environmentKENTIX system socketRJ45 jack for connecting external expansion modulesControl of external alarm systemsControl of Kentix AlarmManager via EthernetControl of external intrusion detection systems with forced operation via IO contactsDimensions90 x 90 x 45 mm WxHxD, weight approx. 100gEnvironmental conditionsTemperature 0 to 50°C, humidity 5-95%, non-condensingProtection classIP20MountingWall/ceiling mounting with wall bracketVersionsKXP-16-B (Housing Black, 868MHz) KXP-16-B-BLE (Black case, BLE 2.4GHz) KXP-16-W-BLE (Housing White, BLE 2.4GHz)Scope of deliveryMounting bracket, mounting material, radio antenna, SlimLine cable 3mAccessoriesPoE Injector (KPOE150S) IO Adapte (KIO3)CertificationCE, FCC		
(depending on version)max. 20m depending on building structure/environmentKENTIX system socketRJ45 jack for connecting external expansion modulesControl of external alarm systemsControl of Kentix AlarmManager via EthernetControl of external intrusion detection systems with forced operation via IO contactsDimensions90 x 90 x 45 mm WxHxD, weight approx. 100gEnvironmental conditionsTemperature 0 to 50°C, humidity 5-95%, non-condensingProtection classIP20MountingWall/ceiling mounting with wall bracketKXP-16-B (Housing Black, 868MHz) KXP-16-W-BLE (Black case, BLE 2.4GHz) KXP-16-W-BLE (Housing White, BEE 2.4GHz)Scope of deliveryMounting bracket, mounting material, radio antenna, SlimLine cable 3mAccessoriesPoE Injector (KPOE150S) IO Adapte (KIO3)	110010 0001 1111	
Control of external alarm systems Control of Kentix AlarmManager via EthernetControl of external intrusion detection systems with forced operation via IO contacts Dimensions 90 x 90 x 45 mm WxHxD, weight approx. 100g Environmental conditions Temperature 0 to 50°C, humidity 5-95%, non-condensing Protection class IP20 Wall/ceiling mounting with wall bracket KXP-16-B (Housing Black, 868MHz) KXP-16-W (Housing White, 868MHz) KXP-16-B-BLE (Black case, BLE 2.4GHz) KXP-16-B-BLE (Housing White, BLE 2.4GHz) Scope of delivery Mounting bracket, mounting material, radio antenna, SlimLine cable 3m PoE Injector (KPOE150S) IO Adapte (KIO3)		
external intrusion detection systems with forced operation via IO contacts Dimensions 90 x 90 x 45 mm WxHxD, weight approx. 100g Environmental conditions Temperature 0 to 50°C, humidity 5-95%, non-condensing Protection class IP20 Mounting Wall/ceiling mounting with wall bracket KXP-16-B (Housing Black, 868MHz) KXP-16-W (Housing White, 868MHz) KXP-16-B-BLE (Black case, BLE 2.4GHz) KXP-16-W-BLE (Housing White, BLE 2.4GHz) Scope of delivery Mounting bracket, mounting material, radio antenna, SlimLine cable 3m PoE Injector (KPOE150S) IO Adapte (KIO3)	KENTIX system socket	RJ45 jack for connecting external expansion modules
Environmental conditions Temperature 0 to 50°C, humidity 5-95%, non-condensing Protection class IP20 Wall/ceiling mounting with wall bracket KXP-16-B (Housing Black, 868MHz) KXP-16-W (Housing White, 868MHz) KXP-16-B-BLE (Black case, BLE 2.4GHz) KXP-16-W-BLE (Housing White, BLE 2.4GHz) Scope of delivery Mounting bracket, mounting material, radio antenna, SlimLine cable 3m PoE Injector (KPOE150S) IO Adapte (KIO3)		external intrusion detection systems with forced operation via
Protection class IP20 Wall/ceiling mounting with wall bracket KXP-16-B (Housing Black, 868MHz) KXP-16-W (Housing White, 868MHz) KXP-16-B-BLE (Black case, BLE 2.4GHz) KXP-16-W-BLE (Housing White, BLE 2.4GHz) Scope of delivery Mounting bracket, mounting material, radio antenna, SlimLine cable 3m PoE Injector (KPOE150S) IO Adapte (KIO3)	Dimensions	90 x 90 x 45 mm WxHxD, weight approx. 100g
MountingWall/ceiling mounting with wall bracketVersionsKXP-16-B (Housing Black, 868MHz) KXP-16-W (Housing White, 868MHz) KXP-16-B-BLE (Black case, BLE 2.4GHz) KXP-16-W-BLE (Housing White, BLE 2.4GHz)Scope of deliveryMounting bracket, mounting material, radio antenna, SlimLine cable 3mAccessoriesPoE Injector (KPOE150S) IO Adapte (KIO3)	Environmental conditions	Temperature 0 to 50°C, humidity 5-95%, non-condensing
Versions KXP-16-B (Housing Black, 868MHz) KXP-16-W (Housing White, 868MHz) KXP-16-B-BLE (Black case, BLE 2.4GHz) KXP-16-W-BLE (Housing White, BLE 2.4GHz) Mounting bracket, mounting material, radio antenna, SlimLine cable 3m PoE Injector (KPOE150S) IO Adapte (KIO3)	Protection class	IP20
Versions KXP-16-W (Housing White, 868MHz) KXP-16-B-BLE (Black case, BLE 2.4GHz) KXP-16-W-BLE (Housing White, BLE 2.4GHz) Mounting bracket, mounting material, radio antenna, SlimLine cable 3m PoE Injector (KPOE150S) IO Adapte (KIO3)	Mounting	Wall/ceiling mounting with wall bracket
Accessories cable 3m PoE Injector (KPOE150S) IO Adapte (KIO3)	Versions	KXP-16-W (Housing White, 868MHz) KXP-16-B-BLE (Black case, BLE 2.4GHz)
IO Adapte (KIO3)	Scope of delivery	g g
Certification CE, FCC	Accessories	
	Certification	CE, FCC