DoorLock KXC-WA3-OUTDOOR – Datasheet

ORDER-CODES:
KXC-WA3-IP2-OUTDOOR

Function	Wall reader for surface mounting
Connection possibility	DoorLock AccessManager (ART: KXP-2-RS)
Configuration	About KentixONE
RFID Reader 13.56MHz	MIFARE® DESFire® MIFARE® Classic, LEGIC prime LEGIC advant, ISO14443A (CSN / UID) ISO15693 (CSN / UID) Sony FeliCa (CSN / UID) Inside Secure (CSN / UID)

© Kentix GmbH. This file was automatically generated on 2026-09-07 10:54:11. Please visit docs.kentix.com for the latest documentation.

Dimensions	90 x 90 x 40mm WxHxD
LED	RED, GREEN
Acoustic signal generator	70dB, 2.3kHz
Connection of wall reader to AccessManager	4-wire cable (cable: J-Y(ST)Y, 4x2x0.8) Cable length up to max. 500m
Addressing **Terminating resistor**	Coding switch (default address: 1) ORIENTATION: (1) **ADDRESS 1(ON/OFF**) (2) ADDRESS 2 (**ON/OFF**) (3) – (4) – (5) CONSTRUCTION RATE**(ON**) (6) – (7) – (8) CONCLUSION RESISTANCE (**ON/OFF**)
Communication	2-wire RS485, encrypted (AES128)
Environment	Temperature -25°C to +60°C
Power supply	10-30VDC, power consumption 2.0W
Connection	9-pin connection terminal detachable CONNECTION: (1) – (2) – (3) – (4) – (5) – (6) DATA-A (7) DATA-B (8) 10-30VDC (9) GND
Protection class	IP66
Scope of delivery	Wall reader
Certification	CE

© Kentix GmbH. This file was automatically generated on 2026-09-07 10:54:11. Please visit docs.kentix.com for the latest documentation.