

DoorLock KXC-WA5 - DATASHEET



ORDER-CODES:
KXC-WA5-IP2

| | |
|----------------------------------|--|
| Function | Biometric wall reader for surface mounting and 2-factor verification |
| Connection possibility | DoorLock AccessManager (ART: KXP-2-RS) |
| Configuration | About KentixONE |
| RFID Reader 13.56MHz | MIFARE® DESFire® MIFARE® Classic, LEGIC prime |
| Dimensions | 88 x 123 x 55 mm WxHxD |
| LED | RED, GREEN |
| Acoustic signal generator | 80dB, 2.3kHz |

| | |
|---|---|
| Connection of wall reader to AccessManager | 4-wire cable (cable: J-Y(ST)Y, 4x2x0.8) Cable length up to max. 500m |
| Addressing Terminating resistor | <p>Coding switch (default address: 1) ASSIGNMENT DIP 1: (1) ADDRESS 1(ON/OFF) (2) ADDRESS 2 (ON/OFF) (3) – (4) – (5) – (6) BAUD RATE(ON) (7) BAUD RATE(OFF) (8) TERMINATING RESISTOR (ON/OFF)</p> <p>ASSIGNMENT DIP 2: (1) TERMINATING RESISTOR (ON/OFF) (2) –</p> |
| Communication | 2-wire RS485, encrypted (AES128) |
| Environment | Temperature -10°C to +55°C |
| Power supply | 10-30VDC, power consumption 1.9W |
| Connection | <p>5-pole terminal block detachable MOVEMENT: (1) 10-30VDC (2) GND (3) DATA-A (4) DATA-B (5) –</p> |
| Protection class | IP54 |
| Scope of delivery | Wall reader |
| Exams | CE |