



ORDER-CODES:

KXC-RA2-14, KXC-RA2-23

<b>Function</b>	Radio RFID cabinet lock with battery power supply
<b>Connection possibility</b>	DoorLock AccessManager KXP-16
<b>RFID reader</b>	13.56MHz Mifare Classic, DESfire
<b>Dimensions</b>	Höhe=148,4mmBreite=44,6mmTiefe=35,9mm
<b>LED</b>	RED, GREEN
<b>Radio</b>	Radio frequency 868 MHz, encryption AES 128 bit, radio range up to 25m depending on building structure/environment up to 16 online cabinet locks per AccessManager
<b>Usage</b>	Installation in cabinet doors with a door thickness of up to 20mm, Suitable for wooden, steel and aluminum doors, Different closing levers included in the scope of delivery

<b>Power supply</b>	1 battery AA lithium 3.6V (ER14505) Up to 100,000 operations with one battery or approx. 8 years
<b>Material</b>	Plastic
<b>Environmental conditions</b>	Temperature -10°C to 55°C for indoor use
<b>Variants</b>	KXC-RA1 (locking bolt: 21mm) KXC-RA2 (locking bolt: 14mm)
<b>Scope of delivery</b>	Cabinet lock, 3x locking lever, fixing material, battery
<b>Accessories</b>	Replacement battery AA Lithium 3.6V (ER14505) Battery change tool
<b>Exams</b>	CE