DoorLock-WA4-V2 – Datasheet



ORDER-CODES:
KXC-WA4-IP2-V2, KXC-WA4-IP1-V2

Function	Wall reader for surface mounting
Connection possibility	DoorLock AccessManager (ART: KXP-2-RS)
Configuration	About KentixONE
RFID Reader 13.56MHz	MIFARE® DESFire® MIFARE® Classic, LEGIC prime LEGIC advant, ISO14443A (CSN / UID) ISO15693 (CSN / UID) Sony FeliCa (CSN / UID) Inside Secure (CSN / UID)
Dimensions	90 x 90 x 40mm WxHxD

© Kentix GmbH. This file was automatically generated on 2026-11-12 13:58:54. Please visit docs.kentix.com for the latest documentation.

LED	RED, GREEN
Acoustic signal generator	70dB, 2.3kHz
Connection of wall reader to AccessManager	4-wire cable (cable: J-Y(ST)Y, 4x2x0.8) Cable length up to max. 500m
Addressing	About AccessManager and teach-in sequence
Communication	2-wire RS485, encrypted (AES128)
Environment	Temperature -25°C to +60°C
Power supply	24VDC (12-28VDC) via AccessManager
Connection	8-pin connection terminal (X1) detachable CONNECTION: (3) DATA-A (4) DATA-B (7) 24VDC (8) GND
Protection class	IP66
Scope of delivery	Wall reader
Certification	CE

© Kentix GmbH. This file was automatically generated on 2026-11-12 13:58:54. Please visit docs.kentix.com for the latest documentation.