

MultiSensor-Door - DATASHEET



ORDER-CODES:

KMS-DOOR-B-BLE, KMS-DOOR-W-BLE

Function	MultiSensor for room monitoring with battery supply
Connection possibility	AlarmManager-PRO (ART: KAM-PRO-x) MultiSensor-LAN-RF (ART: KMS-LAN_RF-x)
Sensor - temperature	Measuring range -20 to 99°C (accuracy $\pm 0.5^{\circ}\text{C}$)
Sensor - Relative humidity	Measuring range 0 to 100% (accuracy $\pm 3\%$)
Sensor - dew point	Calculated in $^{\circ}\text{C}$
Sensor - Vibration	3-axis accelerometer with position detection (sensitivity adjustable), measuring range 0.25-5G
Sensor - Sabotage	Sabotage message during disassembly
Sensor - door contact	Magnetic sensor for door position (distance approx. 1cm)

Signal generator	65dB, 2.3kHz
LED	Multicolor LED (red/green) Alarm (red) Door contact, teach-in (green/green-blinking)
Radio	ZigBee® 2.4GHz ISM Band +3dBm Output Power. IEEE802.15.4 Encryption AES 128 bit
Power supply	Lithium Ion battery, 1/2 AA 3.6V (TYPE: LS14250, 1200 mAh), battery life up to 4 years
Housing	Material: PS 63 x 29 x 28 mm Weight approx. 50g Colors: White, Black
Environmental conditions	Temperature 0 - 45°C Humidity 5-95%, non-condensing
Types	KMS-DOOR-B (Black housing) KMS-DOOR-W (White housing)
Scope of delivery	1x Li-battery 3.6V/1200mAh Assembly material Door contact magnet
Exams	CE