



Legacy product

This product is no longer available. The documentation is still available as an archive.

ORDER-CODES:

KMS-DOOR-B/W

Function	MultiSensor for room monitoring with battery supply
Connection possibility	MultiSensor-LAN-BLE (ART: KMS-LAN-x-BLE) MultiSensor-TI-BLE (ART: KMS-TI-xx-x-BLE)
Sensor - temperature	Measuring range -20 to 99°C (accuracy $\pm 0.5^\circ\text{C}$)
Sensor - Relative humidity	Measuring range 0 to 100% (accuracy $\pm 3\%$)
Sensor - dew point	Calculated in °C
Sensor - Vibration	3-axis accelerometer with position detection (sensitivity adjustable), measuring range 0.25-5G
Sensor - Sabotage	Sabotage message during disassembly

Sensor - door contact	Magnetic sensor for door position (distance approx. 1 cm)
Signal generator	65dB, 2.3kHz
LED	Multicolor LED (red/green) Alarm (red) Door contact, teach-in (green/green-blinking)
Radio	BLE 2,4GHz ISM Band, Verschlüsselung AES 128 Bit
Power supply	Lithium Ion battery, 1/2 AA 3.6V (TYPE: LS14250, 1200 mAh), battery life up to 4 years
Housing	Material: PS 63 x 29 x 28 mm Gewicht ca. 50g Farben: Weiß, Schwarz
Environmental conditions	Temperature 0 - 45°C Humidity 5-95%, non-condensing
Types	KMS-DOOR-B-BLE (Gehäuse Schwarz) KMS-DOOR-W-BLE (Gehäuse Weiß)
Scope of delivery	1x Li-battery 3.6V/1200mAh Assembly material Door contact magnet
Zertifizierung	CE