Passive PDU 40U, 1/3×16/32A (up to 22kVA) – Datasheet



ORDER-CODES:
KPMDU-EM-2406C13C19-1-32, KPMDU-EM-2406C13C19-3-32, KPMDU-EM-4800C13C19-1-32, KPMDU-EM-4800C13C19-1-32

Types	**KPMDU-EM-2406C13C19-1-32 (7.3kVA)** **KPMDU-EM-2406C13C19-3-32 (22kVA)** **KPMDU-EM-4800C13C19-1-32 (7.3kVA)** **KPMDU-EM-4800C13C19-3-32 (22kVA)**
Rated power, voltage	max. 22kVA, 230/400V, depending on configuration
Connector plug	IEC60309, CEE-32A, L1/L2/L3/N/PE/6h
Connection cable	Length 3m, rubber sheathed cable H07RN-F-5G6
Sockets C13 (IEC60320)	24 / 48
Sockets C19 (IEC60320)	6 / 0
Interlock	IEC-LOCK for C13/C19
Fuse/circuit breaker	3/6 x 10A C-type, interlocked 3 x 16A C-type, interlocked
Optical signaling	RED/GREEN representation for backup state
Housing	Sheet metal, powder-coated RAL9005 Protection class 1, protection rating IP20
Size	1770 x 78.2 x 62.5 mm (HxWxD)
Weight	approx. 9,0kg
Environmental conditions	0°C to 60°C, humidity 5-95% Storage temperature: -20°C to 60°C
Certification	CE (2014/35/EC, 2011/65/EU)
Electrical safety	DGUV V3 testing, VDE 0105-100
Marking	Serial number (barcode) Additional free labeling area front panel (60x20mm)

© Kentix GmbH. This file was automatically generated on 2026-11-24 13:09:19. Please visit docs.kentix.com for the latest documentation.