

# Passive PDU 40U, 1/3×16/32A (up to 22kVA) - Datasheet



**ORDER-CODES:**

[KPMDU-EM-2406C13C19-1-32](#), [KPMDU-EM-2406C13C19-3-32](#), [KPMDU-EM-4800C13C19-1-32](#), [KPMDU-EM-4800C13C19-3-32](#)

<b>Types</b>	<b>KPMDU-EM-2406C13C19-1-32 (7.3kVA)</b> <b>KPMDU-EM-2406C13C19-3-32 (22kVA)</b> <b>KPMDU-EM-4800C13C19-1-32 (7.3kVA)</b> <b>KPMDU-EM-4800C13C19-3-32 (22kVA)</b>
<b>Rated power, voltage</b>	max. 22kVA, 230/400V, depending on configuration
<b>Connector plug</b>	IEC60309, CEE-32A, L1/L2/L3/N/PE/6h
<b>Connection cable</b>	Length 3m, rubber sheathed cable H07RN-F-5G6
<b>Sockets C13 (IEC60320)</b>	24 / 48
<b>Sockets C19 (IEC60320)</b>	6 / 0
<b>Interlock</b>	IEC-LOCK for C13/C19
<b>Fuse/circuit breaker</b>	3/6 x 10A C-type, interlocked 3 x 16A C-type, interlocked
<b>Optical signaling</b>	RED/GREEN representation for backup state
<b>Housing</b>	Sheet metal, powder-coated RAL9005 Protection class 1, protection rating IP20
<b>Size</b>	1770 x 78.2 x 62.5 mm (HxWxD)
<b>Weight</b>	approx. 9,0kg
<b>Environmental conditions</b>	0°C to 60°C, humidity 5-95% Storage temperature: -20°C to 60°C
<b>Certification</b>	CE (2014/35/EC, 2011/65/EU)
<b>Electrical safety</b>	DGUV V3 testing, VDE 0105-100
<b>Marking</b>	Serial number (barcode) Additional free labeling area front panel (60x20mm)