

SiteManager without mobile radio - Datasheet



Legacy product

This product is no longer available. The documentation is still available as an archive.

ORDER-CODES: KSM-DR-01

Function	Central processing unit with KentixONE High-Performance ARM Processor Quad Core 1.6 GHz, fanless 32GB Flash, 4GB RAM
Integrated software	KentixONE via integrated web server (HTTPS)
Quantity devices	Up to 250 devices can be managed (LAN, RADIO)



IP Ports	Web server: 443 TCP (also communication with sensors etc.) SNMP-GET: 161 UDP SNMP-TRAP: 162 UDP KentixONE-GO: 5222 TCP
Signal generator	85dB, 2.3kHz
LED	RUN/POWER (Green)
Real-time clock	Battery buffered clock (Battery: CR1220, approx. 10 years)
Ethernet	LAN1: 1Gbit (default IP: 192.168.100.222) LAN2: 100Mbit (default IP: 192.168.101.222)
SD card	Integrated Micro SD card holder as additional memory for image recording
Power supply	24VDC +-20%, power consumption approx. 5W Plug: WAGO item no. 714-102 (MCS MINI SL)
Button	Reset button for factory reset on rear panel
Housing	Metal housing, 111 x 25 x76 mm (HxWxD) Weight approx. 300g DIN rail holder, 35mm
Environmental conditions	Temperature 0 - 55° C Humidity 93% @ 40° C, non-condensing Operating altitude: 5000 m (16400 ft)
Types (ART-NO)	KSM-DR1 (Housing Black)
Scope of delivery	Power supply 24VDC, SlimLine cable 3m
Accessories	19" 4U mounting frame with dual power supply (KRA-04-DP24)
Certification	CE