

# SiteManager without mobile radio - Datasheet



## Legacy product

This product is no longer available. The documentation is still available as an archive.

### ORDER-CODES:

[KSM-DR-01](#)

<b>Function</b>	Central processing unit with KentixONE High-Performance ARM Processor Quad Core 1.6 GHz, fanless 32GB Flash, 4GB RAM
<b>Integrated software</b>	KentixONE via integrated web server (HTTPS)
<b>Quantity devices</b>	Up to 250 devices can be managed (LAN, RADIO)

<b>IP Ports</b>	Web server: 443 TCP (also communication with sensors etc.) SNMP-GET: 161 UDP SNMP-TRAP: 162 UDP KentixONE-GO: 5222 TCP
<b>Signal generator</b>	85dB, 2.3kHz
<b>LED</b>	RUN/POWER (Green)
<b>Real-time clock</b>	Battery buffered clock (Battery: CR1220, approx. 10 years)
<b>Ethernet</b>	LAN1: 1Gbit (default IP: 192.168.100.222) LAN2: 100Mbit (default IP: 192.168.101.222)
<b>SD card</b>	Integrated Micro SD card holder as additional memory for image recording
<b>Power supply</b>	24VDC +-20%, power consumption approx. 5W Plug: WAGO item no. 714-102 (MCS MINI SL)
<b>Button</b>	Reset button for factory reset on rear panel
<b>Housing</b>	Metal housing, 111 x 25 x76 mm (HxWxD) Weight approx. 300g DIN rail holder, 35mm
<b>Environmental conditions</b>	Temperature 0 - 55°C Humidity 93% @ 40°C , non-condensing Operating altitude: 5000 m (16400 ft)
<b>Types (ART-NO)</b>	KSM-DR1 (Housing Black)
<b>Scope of delivery</b>	Power supply 24VDC, SlimLine cable 3m
<b>Accessories</b>	19" 4U mounting frame with dual power supply (KRA-04-DP24)
<b>Certification</b>	CE